

206 Jones Blvd. Pottstown, PA 19464 USA
Phone: 610-495-0110 : 800-223-2629
www.micro-coax.com

UTiFLEX Flexible Microwave Cable Assemblies

MECHANICAL CHARACTERISTICS

Outer Diameter, inch (mm)	0.21 (5.33)
Minimum Bend Radius, inch (mm)	0.38 (9.65)
Flexures	10,000
Weight , grams/ft. (meter)	22 (72.2)

ELECTRICAL CHARACTERISTICS

Impedance(ohms)	50
Frequency Range (GHz)	0.05 - 26.5
Velocity of Propagation	77%
Capacitance, pF/ft. (pF/meter)	26.2 (85.96)
Shielding Effectiveness, dB @ 1GHz	>100
Maximum Insertion Loss , dB/ft. (dB/meter)	Frequency

Insertion Loss per Catalog

1.0 GHz	0.08 (0.26)
10.0 GHz	0.27 (0.89)
18.0 GHz	0.38 (1.25)
26.5 GHz	0.48 (1.57)
40.0 GHz	N/A ()
50.0 GHz	N/A ()


Phase Stability Versus Flexure	10 GHz: 3° 18 GHz: 5°
VSWR	Based on connector selections.

ENVIRONMENTAL CHARACTERISTICS

Temperature Range(Deg C)	-65/+165
--------------------------	----------

MATERIALS


Outer jacket	Fluorinated Ethylene Propylene (FEP)
Braid	SPC Braid
Outer Conductor	Silver plated copper tape
Dielectric	LD PTFE
Center Conductor	Solid SPC




**Not typical for UGN070D

CHARTS

MAXIMUM INSERTION LOSS




PHASE STABILITY VS. TEMPERATURE



Phase Chart

POWER HANDLING



Power Chart
Average Power Handling, Watts CW at 20 degrees Celsius and Sea level